



GEMINI PLUS ESP15-25

Type	ESP15-25
Input voltage variation	±25 %
Rated power	15 kVA
Input voltage range	172-288 V
Max input current	87 A
Output voltage	230 V
Rated output current	65 A
Efficiency	>98 %
Adjustment speed	one cycle
Dimensions WxDxH	410x680x1200mm
Weight	120 kg



Standard features

Voltage regulation	IGBT controlled
Selectable output voltage	220-230-240V
Frequency	50Hz ±5% or 60Hz ±5%
Output voltage accuracy	±0.5%
Admitted load variation	Up to 100%
Cooling	Forced ventilation
Ambient temperature	-25/+45°C
Storage temperature	-25/+60°C
Max relative humidity	<95% (non condensing)
Admitted overload	150% 2sec.
Colour	RAL 9005
Protection degree	IP 21
Instrumentation	Output digital voltmetre
Installation	Indoor
Overvoltage protection	Class II output surge arrestors
Protections	EMI/RFI filters
	Input circuit breaker
	Protection by-pass (automatic)
	Maintenance by-pass (manual)

Optional Standard Accessories

Load protection against over/undervoltage ABB / SCHNEIDER	PS ABB / SCHNEIDER 80
Single-phase input isolation transformer	108A