



GEMINI PLUS ESP7-30

| | |
|-------------------------|----------------|
| Type | ESP7-30 |
| Input voltage variation | ±30 % |
| Rated power | 7 kVA |
| Input voltage range | 161-300 V |
| Max input current | 43 A |
| Output voltage | 230 V |
| Rated output current | 30 A |
| Efficiency | >98 % |
| Adjustment speed | one cycle |
| Dimensions WxDxH | 410x530x1200mm |
| Weight | 57 kg |



Standard features

| | |
|---------------------------|---------------------------------|
| Voltage regulation | IGBT controlled |
| Selectable output voltage | 220-230-240V |
| Frequency | 50Hz ±5% or 60Hz ±5% |
| Output voltage accuracy | ±0.5% |
| Admitted load variation | Up to 100% |
| Cooling | Forced ventilation |
| Ambient temperature | -25/+45°C |
| Storage temperature | -25/+60°C |
| Max relative humidity | <95% (non condensing) |
| Admitted overload | 150% 2sec. |
| Colour | RAL 9005 |
| Protection degree | IP 21 |
| Instrumentation | Output digital voltmetre |
| Installation | Indoor |
| Overvoltage protection | Class II output surge arrestors |
| Protections | EMI/RFI filters |
| | Input circuit breaker |
| | Protection by-pass (automatic) |
| | Maintenance by-pass (manual) |

Optional Standard Accessories

| | |
|---|-----------------------|
| Load protection against over/undervoltage ABB / SCHNEIDER | PS ABB / SCHNEIDER 32 |
| Single-phase input isolation transformer | 43A |