

## HP10-60HZ-230V MICROFIX

<b>Product code</b>	IB3DBB160060987
<b>Reactive power Ue=230V</b>	6 kvar
<b>Nominal voltage Ue</b>	230V
<b>Capacitors voltage Un</b>	415 V
<b>Capacitors max voltage Umax</b>	455 V
<b>Frequency</b>	60 Hz
<b>THDI<sub>R</sub>%</b>	≤20%
<b>THDIC%</b>	≤70%
<b>Load break switch</b>	40 A
<b>Icc</b>	50 kA
<b>IP degree</b>	IP3X
<b>Dimensions WxDxH</b>	310x200x450mm
<b>Weight</b>	12 kg

NOTE Icc value: Other values upon request. Short-circuit withstand current conditioned by the upstream protective device.

### Standard features

<b>Max current overload I<sub>n</sub></b>	1.3 I <sub>n</sub>
<b>Max current overload I<sub>n</sub> (capacitors)</b>	1,3 I <sub>n</sub> (continuous)
<b>Max overload V<sub>n</sub></b>	1,1xU <sub>e</sub>
<b>Max overload V<sub>n</sub> (capacitors)</b>	3xU <sub>n</sub> (for 1 minute)
<b>Insulation voltage</b>	690V
<b>Temperature class</b>	-5/+40°C
<b>Temperature class (capacitors)</b>	-25/+55°C
<b>Discharge device</b>	mounted on each bank
<b>Installation</b>	indoor
<b>Service</b>	continuous
<b>Internal connection</b>	delta
<b>Total losses</b>	~ 2W/kvar
<b>Inner surface finish</b>	zinc passivation
<b>Standards (bank)</b>	IEC 61439-1/2, IEC 61921
<b>Standards (capacitors)</b>	IEC 60831-1/2

### Generalities

Zinc-passivated metallic enclosure painted with epossidic dust paint, colour RAL 7035.

Load-break switch with door interlock.

Fuses with high breaking power NH00-gG.

FS17 450/750V self-extinguish cable according to EN 50525 - EN 50575 - EN 50575/A1.

IP3X protection degree.

CRM25 single phase self-healing metallized polypropylene capacitor with Un=415V-50Hz (350V60Hz) rated voltage.

Discharge resistance.

Signal lamp power on.

