VEGA 0.7-15/25

Type	0.7-15/25
Input voltage variation	+15/-25 %
Rated power	0.7 kVA
Input voltage range	172-265 V
Max input current	4 A
Output voltage	230 V
Rated output current	3 A
Efficiency	>96 %
Adjustment speed	12 ms/V
Dimensions WxDxH	300x460x300mm
Weight	17 kg

Standard features

Selectable output voltage	220-230-240V (dip switch)
Frequency	50Hz ±5% or 60Hz ±5%
Output voltage accuracy	±0,5%
Admitted load variation	Up to 100%
Cooling	Natural ventilation
Ambient temperature	-25/+45°C
Storage temperature	-25/+60°C
Max relative humidity	<95% (non condensing)
Admitted overload	200% 2min.
Harmonic distortion	None introduced
Colour	RAL 7035
Protection degree	IP 21
Instrumentation	Output digital voltmetre
Installation	Indoor

Optional Standard Accessories

Interrupting devices ABB / SCHNEIDER - INPUT	DI ABB / SCHNEIDER 10 - INPUT
Interrupting devices ABB / SCHNEIDER - OUTPUT	DI ABB / SCHNEIDER 10 - OUTPUT
Load protection against over/undervoltage ABB / SCHNEIDER	PS ABB / SCHNEIDER 10
CAM SOCOMEC	CAM10
Single-phase input isolation transformer	8A
SPD Surge arrestors ORTEA	SPD ORTEA INPUT CLASS I 25/2
SPD Surge arrestors ORTEA	SPD ORTEA OUTPUT CLASS II 20/2

R 7 | 9 | 2022