ORION 80-15/35

Type	80-15/35
Input voltage variation	+15/-35 %
Rated power	80 kVA
Input voltage range	260-460 V
Max input current	178 A
Output voltage	400 V
Rated output current	115 A
Efficiency	>98 %
Adjustment speed	10 ms/V
Dimensions WxDxH	600x800x1800mm
Weight	600 kg

Standard features

Voltage stabilisation	Independent phase control
Selectable output voltage	220-230-240V (L-N) / 380-400-415V (L-L)
Frequency	50Hz ±5% or 60Hz ±5%
Output voltage accuracy	±0,5%
Admitted load variation	Up to 100%
Admitted load imbalance	100 %
Cooling	Up to 45kVA ±15% natural ventilation From 60kVA ±15% aided with fans
Ambient temperature	-25/+45°C
Storage temperature	-25/+60°C
Max relative humidity	<95% (non condensing)
Admitted overload	200% 2min.
Harmonic distortion	None introduced
Colour	RAL 7035
Protection degree	IP 21
Instrumentation	Output digital multimetre
Installation	Indoor
Overvoltage protection	Output class II surge arrestors (over 60kVA ±15%)

Optional Standard Accessories

Interrupting devices ABB / SCHNEIDER - INPUT	DI ABB / SCHNEIDER 200 - INPUT
Interrupting devices ABB / SCHNEIDER - OUTPUT	DI ABB / SCHNEIDER 125 - OUTPUT
Load protection against over/undervoltage ABB / SCHNEIDER	PS ABB / SCHNEIDER 125
Disconnector and changeover switch ABB	D-IC ABB 200
Input three-phase isolation transformer DZN0	DZN0 180A
SPD Surge arrestors ORTEA	SPD ORTEA INPUT CLASS I 25/4
SPD Surge arrestors ORTEA	SPD ORTEA OUTPUT CLASS II 20/4

R 27 | 7 | 2022