



# SIRIUS ADVANCE 1600-20

Type	1600-20
System	Three-phase
Input voltage variation	±20 %
Rated power	1600 kVA
Input voltage range	320-480 V
Max input current	2887 A
Output voltage	400 V
Rated output current	2309 A
Efficiency	>98 %
Compensation Duration	Continuous
Adjustment speed	18 ms/V
Dimensions WxDxH	6600x1000x2100mm
Weight	5800 kg



This image is indicative only.

## Standard features

Voltage stabilisation	Independent phase control
Selectable output voltage	from 210V to 255V (L-N) / from 360V to 440V (L-L)
Frequency	50Hz ±5% or 60Hz ±5%
Output voltage accuracy	±0,5%
Admitted load variation	Up to 100%
Admitted load imbalance	100 %
Cooling	Natural ventilation (from 35°C aided with fans)
Ambient temperature	-25/+45°C
Storage temperature	-25/+60°C
Max relative humidity	<95% (non condensing)
Admitted overload	200% 2min.
Harmonic distortion	None introduced
Colour	RAL 7035
Protection degree	IP 21
Instrumentation	10" touch panel (multilingual) remotely available via VNC Reactive power regulator
Installation	Indoor
Communication system	Ethernet / USB / MODBUS / Ortea XCloud
Overvoltage protection	Class I input surge arrestors Class II output surge arrestors Optimal voltage return through supercapacitors in case of black-out
By-pass and total protection kit	Input automatic circuit breaker By-pass switch made of an interlocked automatic circuit breaker Output interlocked motorized automatic circuit breaker with protection against overload, overvoltage, undervoltage, phase sequence error and phase failure
Integrated PFC automatic systems	Based on high-energy density metallized polypropylene three-phase capacitors Un = 525V Three-phase blocking reactor (tuning frequency 180Hz)

## Optional Accessories

Input three-phase isolation transformer DZNO	DZNO 2890A
--	------------



EMI/RFI filters

FL 2500