



FH20-60HZ-400V MULTIMATIC

Product code	IN7AFF388060701
Reactive power Ue=400V	880 kvar
Nominal voltage Ue	400V
Capacitors voltage Un	550 V
Capacitors max voltage Umax	600 V
Frequency	60 Hz
THDI _R %	100%
I _{250Hz} %	≤25%
THDV _R %	≤6%
Detuning frequency f _D	216 Hz
Steps	80-5x160 kvar
Electrical steps number	11
Banks	11x80 kvar
Load break switch	2x1250 A
lcc	50 kA
Controller	8BGA
IP degree	IP4X
Dimensions WxDxH	1220x670x2360mm
Weight	962 kg



This image is indicative only.

NOTE Icc value: Other values upon request.

Standard features

Max current overload In	1.3 ln
Max current overload In (capacitors)	1,3 In (continuous)
Max overload Vn	1,1xUe
Max overload Vn (capacitors)	3xUn (for 1 minute)
Insulation voltage	690V
Temperature class	-5/+40°C
Temperature class (capacitors)	-25/+55°C
Discharge device	mounted on each bank
Installation	indoor
Service	continuous
Internal connection	delta
Total losses	~ 6W/kvar
Inner surface finish	zinc passivation
Standards (bank)	IEC 61439-1/2, IEC 61921
Standards (capacitors)	IEC 60831-1/2



POWER FACTOR CORRECTION SOLUTIONS WITH HIGH GRADIENT METALLIZED POLYPROPYLENE CAPACITORS



Generalities

Zink-passivated metallic enclosure painted with epossidic dust paint, colour RAL 7035.

Auxiliary transformer to separate power and auxiliary circuit parts (110V).

Load-break switch with door interlock.

Contactors for capacitive loads.

FS17 450/750V self-extinguish cable according to EN 50525 - EN 50575 - EN 50575/A1.

Microprocessor Power Factor Correction relay.


Control and protection multimeter MCP5, integrated in 8BGA controller.

CRM25 single phase self-healing metallized polypropylene capacitor with Un=550V-50Hz (480-V60Hz) rated voltage.


Three phase detuning choke with tuning frequency fD=216Hz (N=3.6-p%=7.7%).











Bottom view ground fixing and

