



OXYGEN K 1250-15-50K

| | |
|--------------------------------|------------------|
| Type | 1250-15-50K |
| Input voltage variation | ±15 (-50) % |
| Rated power | 1250 kVA |
| Input voltage range | 340-460 V |
| Max input current | 2123 A |
| Output voltage | 400 V |
| Rated output current | 1804 A |
| Efficiency | >98 % |
| Adjustment speed | ms/V |
| Dimensions WxDxH | 6000x1400x2400mm |
| Weight | 6600 kg |

Standard features

| | |
|----------------------------------|--|
| Voltage regulation | IGBT controlled (double conversion technology) |
| Voltage stabilisation | Independent phase control |
| Selectable output voltage | 380-400-415V (440-460-480V**) |
| Frequency | 50Hz ±5% or 60Hz ±5% |
| Output voltage accuracy | ±0,5% |
| Admitted load variation | Up to 100% |
| Admitted load imbalance | 100 % |
| Cooling | Forced ventilation |
| Ambient temperature | 0/+40°C |
| Storage temperature | 0/+60°C |
| Max relative humidity | <95% (non condensing) |
| Admitted overload | 150% for 1 minute (at nominal input voltage) |
| Colour | RAL 9005 |
| Protection degree | IP2X |
| Instrumentation | 10" touch panel, multilingual (on request remotely available by dedicated software connected to the same Ethernet network) |
| Installation | Indoor |
| Communication system | MODBUS TCP/IP |
| Overvoltage protection | Class I input surge arrestors Class II output surge arrestors |
| Protections | Automatic by-pass protection Input automatic circuit breaker By-pass switch made of an interlocked automatic circuit breaker Output interlocked motorized automatic circuit breaker |

Optional Standard Accessories