

HP10 MINIMATIC IP55

Product code	IJ0AKF311250654
Reactive power Ue=400V	105 kvar
Reactive power Ue=415V	112 kvar
Nominal voltage Ue	400-415V
Capacitors voltage Un	415 V
Capacitors max voltage Umax	455 V
Frequency	50 Hz
THDI _R %	≤12%
THDIC%	≤50%
Steps	7,5-15,22,5-2x30 kvar
Electrical steps number	14
Banks	30-75 kvar
Load break switch	250 A
Icc	9 kA
Controller	5LGA
IP degree	IP55
Dimensions WxDxH	600x440x1500mm
Weight	47 kg

NOTE Icc value: Other values upon request.

Standard features

Max current overload In	1.3 In
Max current overload In (capacitors)	1,3 In (continuous)
	2 In (x380s every 60 minutes)
	3 In (x150s every 60 minutes)
	4 In (x70s every 60 minutes)
	5 In (x45s every 60 minutes)
Max overload Vn	1,1xUe
Max overload Vn (capacitors)	3xUn (for 1 minute)
Insulation voltage	690V
Temperature class	-5/+40°C
Temperature class (capacitors)	-25/+55°C
Discharge device	mounted on each bank
Installation	outdoor
Service	continuous
Internal connection	delta
Total losses	~ 2W/kvar
Inner surface finish	zinc passivation
Standards (bank)	IEC 61439-1/2, IEC 61921
Standards (capacitors)	IEC 60831-1/2



Generalities

- Zink-passivated metallic enclosure painted with epossidic dust paint, colour RAL 7035.
 - Auxiliary transformer to separate power and auxiliary circuit parts (110V).
 - Load-break switch with door interlock.
 - Special contactors with damping resistors to limit capacitors inrush current (AC6b).
 - FS17 450/750V self-extinguish cable according to EN 50525 - EN 50575 - EN 50575/A1.
 - Microprocessor Power Factor Correction relay.
 - CRM25 single phase self-healing metallized polypropylene capacitor with Un=415V rated voltage.
-

