



ORION PLUS 630-30

Type	630-30
Input voltage variation	±30 %
Rated power	630 kVA
Input voltage range	280-520 V
Max input current	1299 A
Output voltage	400 V
Rated output current	909 A
Efficiency	>98 %
Adjustment speed	12 ms/V
Dimensions WxDxH	2400x1000x2200mm
Weight	2630 kg



This image is indicative only.

Standard features

Voltage stabilisation	Independent phase control
Selectable output voltage	from 210V to 255V (L-N) / from 360V to 440V (L-L)
Frequency	50Hz ±5% or 60Hz ±5%
Output voltage accuracy	±0,5%
Admitted load variation	Up to 100%
Admitted load imbalance	100 %
Cooling	Natural ventilation (from 35°C aided with fans)
Ambient temperature	-25/+45°C
Storage temperature	-25/+60°C
Max relative humidity	<95% (non condensing)
Admitted overload	200% 2min.
Harmonic distortion	None introduced
Colour	RAL 7035
Protection degree	IP 21
Instrumentation	Input & Output digital multimeter
Installation	Indoor
Overvoltage protection	Class II output surge arrestors Optimal voltage return through supercapacitors in case of black-out

Optional Standard Accessories

Interrupting devices ABB / SCHNEIDER - INPUT	DI ABB / SCHNEIDER 1600 - INPUT
Interrupting devices ABB / SCHNEIDER - OUTPUT	DI ABB / SCHNEIDER 1000 - OUTPUT
Load protection against over/undervoltage ABB / SCHNEIDER	PS ABB / SCHNEIDER 1000
Disconnecter and changeover switch ABB	D-IC ABB 1600
Automatic circuit breaker and changeover switch ABB	IA-CA ABB 1600
Total protection kit ABB / SCHNEIDER	kit ABB / SCHNEIDER 1600
Input three-phase isolation transformer DZNO	DZNO 1445A



SPD Surge arrestors ORTEA	SPD ORTEA INPUT CLASS I 25/4
Integrated PFC automatic systems from 400kVA to 800kVA	PFC 400-800 630
EMI/RFI filters	FL 1000