



ORION PLUS 400-20

| | |
|-------------------------|-----------------|
| Type | 400-20 |
| Input voltage variation | ±20 % |
| Rated power | 400 kVA |
| Input voltage range | 320-480 V |
| Max input current | 722 A |
| Output voltage | 400 V |
| Rated output current | 577 A |
| Efficiency | >98 % |
| Adjustment speed | 15 ms/V |
| Dimensions WxDxH | 1200x800x2000mm |
| Weight | 1300 kg |



This image is indicative only.

Standard features

| | |
|---------------------------|--|
| Voltage stabilisation | Independent phase control |
| Selectable output voltage | from 210V to 255V (L-N) / from 360V to 440V (L-L) |
| Frequency | 50Hz ±5% or 60Hz ±5% |
| Output voltage accuracy | ±0,5% |
| Admitted load variation | Up to 100% |
| Admitted load imbalance | 100 % |
| Cooling | Natural ventilation (from 35°C aided with fans) |
| Ambient temperature | -25/+45°C |
| Storage temperature | -25/+60°C |
| Max relative humidity | <95% (non condensing) |
| Admitted overload | 200% 2min. |
| Harmonic distortion | None introduced |
| Colour | RAL 7035 |
| Protection degree | IP 21 |
| Instrumentation | Input & Output digital multimeter |
| Installation | Indoor |
| Overvoltage protection | Class II output surge arrestors Optimal voltage return through supercapacitors in case of black-out |

Optional Standard Accessories

| | |
|---|---------------------------------|
| Interrupting devices ABB / SCHNEIDER - INPUT | DI ABB / SCHNEIDER 800 - INPUT |
| Interrupting devices ABB / SCHNEIDER - OUTPUT | DI ABB / SCHNEIDER 630 - OUTPUT |
| Load protection against over/undervoltage ABB / SCHNEIDER | PS ABB / SCHNEIDER 630 |
| Disconnecter and changeover switch ABB | D-IC ABB 800 |
| Automatic circuit breaker and changeover switch ABB | IA-CA ABB 800 |
| Total protection kit ABB / SCHNEIDER | kit ABB / SCHNEIDER 800 |
| Input three-phase isolation transformer DZNO | DZNO 722A |



| | |
|---|------------------------------|
| SPD Surge arrestors ORTEA | SPD ORTEA INPUT CLASS I 25/4 |
| Integrated PFC automatic systems from 400kVA to 800kVA | PFC 400-800 400 |
| EMI/RFI filters | FL 800 |